

AC & DC POWER SUPPLIES

AC POWER SUPPLY PREPACKAGED KITS

MODEL #	TRANS-FORMER(S)	INPUT POWER	HEIGHT	WIDTH	DEPTH	120 VAC OUTLETS	AUX OUTPUT WIRE	ON/OFF SWITCH	MAIN BREAKER ON INPUT POWER *	SECONDARY CONFIGURATION	METAL HOUSING	SUB-PANEL / TRACK MOUNT	SPEC PAGE
CTRL-PS	40 VA	120 Vac	14.500"	7.700"	3.900"			•			MH1000	MT212-4 included	120
MHP3903100AB10	100 VA	120 Vac	12.500"	24.500"	6.500"	•	•	•	10 A Switch/Breaker	Ext. Terminal Strip	MH3900	SP3803S (Polymetal)	120
MHP3903100A100AB10	100 VA, 100 VA	120 Vac	12.500"	24.500"	6.500"	•	•	•	10 A Switch/Breaker	Ext. Terminal Strip	MH3900	SP3803S (Polymetal)	121
MHP3904100AB10	100 VA	120 Vac	12.500"	24.500"	6.500"	•	•	•	10 A Switch/Breaker	Ext. Terminal Strip	MH3900	SP3804S (Perforated)	120
MHP3904100A100AB10	100 VA, 100 VA	120 Vac	12.500"	24.500"	6.500"	•	•	•	10 A Switch/Breaker	Ext. Terminal Strip	MH3900	SP3804S (Perforated)	121
MHP4604100AB10	100 VA	120 Vac	16.150"	20.000"	6.720"	•	•	•	10 A Switch/Breaker	Ext. Terminal Strip	MH4600	SP4604 (Perforated)	121
MHP4604100A100AB10	100 VA, 100 VA	120 Vac	16.150"	20.000"	6.720"	•	•	•	10 A Switch/Breaker	Ext. Terminal Strip	MH4600	SP4604 (Perforated)	122

DC POWER SUPPLIES

MODEL #	UL	VOLTAGE INPUT	VOLTAGE OUTPUT	OUTPUT CURRENT	ON/OFF SWITCH	HEIGHT	WIDTH	DEPTH	HOUSING STYLE / TRACK MOUNT	SPEC PAGE
PSP24DA	•	24 Vac	Adjustable 1.5-28 Vdc ; Non-Isolated	300 mA		2.390"	3.310"	1.810"	Enclosed	122
PSH24DWB10		120 Vac	Fixed 24 Vdc ; Isolated	2.5 Amp	•	4.500"	5.438"	4.500"	Enclosed	123
PSH100A24DWB10		120 Vac	Fixed 24 Vdc ; Isolated 100 VA, 24 Vac	2.5 Amp	•	4.500"	8.625"	4.500"	Enclosed	123
PSMN24DA	•	24 Vac	Adjustable 1.5-28 Vdc ; Non-Isolated	300 mA		1.750"	2.750"	1.750"	MT212-2 included	124
PSMN24DAS	•	24 Vac	Adjustable 1.5-28 Vdc ; Non-Isolated	300 mA	•	1.750"	2.750"	1.750"	MT212-2 included	124
PSM20A12DAS	•	24 Vac	Adjustable 1.5-14 Vdc ; Isolated	300 mA	•	2.750"	4.000"	2.250"	MT212-4 included	124
PSM24A24DAS	•	24 Vac	Adjustable 1.5-28 Vdc ; Isolated	300 mA	•	2.750"	4.000"	2.250"	MT212-4 included	125
PSM19A24DAS	•	120 Vac	Adjustable 1.5-28 Vdc ; Isolated	300 mA	•	2.750"	4.000"	2.250"	MT212-4 included	125
PSMN40A24DS	•	120 Vac	Fixed 24 Vdc ; Isolated	1 Amp	•	5.000"	2.750"	2.500"	MT212-6 included	125
PSH100AB10-DC	•	120 Vac	Fixed 24 Vdc ; Isolated	2.5 Amp	•	4.500"	5.438"	4.500"	Enclosed	126
PSH100A100AB10-DC	•	120 Vac	Fixed 24 Vdc ; Isolated ; 100 VA, 24 Vac	2.5 Amp	•	4.500"	8.625"	4.500"	Enclosed	126

DIN MOUNT DC POWER SUPPLIES

MODEL #	UL	VOLTAGE INPUT	VOLTAGE OUTPUT	OUTPUT CURRENT	ON/OFF SWITCH	HEIGHT	WIDTH	DEPTH	HOUSING STYLE / TRACK MOUNT
PULS-ML15-241	•	100-240 Vac	Adjustable 24-28 Vdc ; Isolated	600 mA		2.950"	0.890"	3.580"	DIN Mount
PULS-PIC120-241D	•	100-120 Vac; 200-240 Vac	Adjustable 24-28 Vdc ; Isolated	5 Amp		4.880"	1.540"	4.880"	DIN Mount
PULS-PIC240-241D	•	100-240 Vac	Adjustable 24-28 Vdc ; Isolated	10 Amp		4.880"	1.930"	4.880"	DIN Mount
PULS-PIM36-241	•	100-240 Vac	Adjustable 24-28 Vdc ; Isolated	1.5 Amp		3.540"	0.860"	3.580"	DIN Mount
PULS-PIM60-241	•	100-240 Vac	Adjustable 24-28 Vdc ; Isolated	2.5 Amp		3.540"	1.420"	3.580"	DIN Mount
PULS-PIM60-245	•	100-240 Vac	Adjustable 24-28 Vdc ; Isolated	2.5 Amp		3.540"	1.420"	3.580"	DIN Mount
PULS-PIM90-241	•	100-240 Vac	Adjustable 24-28 Vdc ; Isolated	3.8 Amp		3.540"	1.420"	3.580"	DIN Mount
PULS-PIM90-245	•	100-240 Vac	Adjustable 24-28 Vdc ; Isolated	3.8 Amp		3.540"	1.420"	3.580"	DIN Mount
PULS-PIM90-245-L1	•	100-240 Vac	Adjustable 24-28 Vdc ; Isolated	3.8 Amp		3.540"	1.420"	3.580"	DIN Mount

For full product information on "PULS-" models, see our website for data sheets pages.

UL = Class 2 UL Listed - see data sheet for specific Listing

* = Kills power to entire unit: Outlets, Aux. Output, & Transformer; Total Combined Output 9A