

Connected products

Easy UPS 1 Phase On Line SRVS



1 to 10 KVA 1 phase ON Line UPS

For small to medium businesses, Easy UPS 1 Ph On-Line provides essential power protection for unstable power conditions, ensuring consistent and reliable connectivity at the most critical moments.

[Product references](#)

+

Flexible design for both high and low powered devices

- Stay connected for hours, not minutes
- Automatic Voltage Regulation (AVR)
- Reliable surge protection
- Wall mounting sockets
- Wide outlet spacing
- Compact size
- Intelligent off-mode charging
- Cold start function
- Easy to use
- Battery self diagnosis

Characteristics

On-Line UPS - Tower for Small and Medium Office / Business			
UPS model	SRS1KI	SRS2KI	SRS3KI
Power Capacity	800 W / 1000 VA	1600 W / 2000 VA	2400 W / 3000 VA
Half Load Runtime (min)	10		
Full Load Runtime (min)	4		
DB-9 RS-232	Supports Windows® 2000/2003/XP/Vista/2008/7/8, Linux, Unix and Mac		
Intelligente slot	Mini Slot		
Control panel & audible alarms	Multi function LCD status and control console		
Surge energy rating (Joules)	600 J		
Physical and Warranty			
Dimension D x W x H (mm)	288 x 145 x 223	400 x 145 x 238	425 x 190 x 336
Weight (kgs)	9.3	16.8	26.8
Regulatory	CE		
Warranty	2 years		
Input Connection	IEC C14		IEC C20
Output Connections	IEC C13	IEC C13	IEC C13, C19
Accessories	ApVS9601 Schneider Electric Easy UPS Online SNMP Card		

Easy UPS 1Ph line interactive SMVS



[Product references](#)

+

LCD Display: intuitive interface provides comprehensive status information at a glance

Pure Sine-Wave Output: provides optimum device compatibility when on battery

Automatic Voltage Regulation

Communication Ports: USB and serial ports for UPS management

Generous number of outlets: all receptacles are surge and UPS output protected

Rugged Sheet Metal Construction: rigidly holds and protects critical electrical components

Battery connector: convenient way to disconnect battery for transport.

Safety-agency approved: ensures the product has been tested and approved to national standards

750 to 3000 VA 1 phase line interactive UPS

Easy UPS Line-Interactive Sinewave SMVS is a versatile uninterruptable power supply developed to handle a wide voltage range in regions with inconsistent power conditions while also delivering quality that millions of professionals trust around the world.

Characteristics

Line - interactive UPS - Tower (network card not available)					
UPS model	SMVS750CAI	SMVS1000CAI	SMVS1500CAI	SMVS2000CAI	SMVS3000CAI
Power Capacity	525 W / 750 VA	700 W / 1000 VA	1050 W / 1500 VA	1400 W / 2000 VA	2100 W / 3000 VA
Typical recharge time	4-6 hours recover to 90% capacity				
Full Load Runtime (min)	> 2 mins 30 secs				
RS-232	Supports Windows 2000/2003/XP/Vista/2008/7/8, Linux, Unix and Mac				
Intelligente slot	Mini Slot				
Dry contact	Multi function LCD status and control console				
USB port	Supports Windows® 7 / Server 2012 / 10 / Sever 2016				
LCD display	AC Mode, AVR Mode, Battery Mode, Battery Level, Load Level, Input Voltage, Output Voltage, System Error, Battery Malfunction				
Physical and Warranty					
Dimension D x W x H (mm)	416 x 160 x 220			455 x 180 x 240	
Weight (kgs)	13.6	13.6	17.8	23.5	25.2
Regulatory	CE				
Warranty	2 years				
Input Connection	IEC C14				IEC C20
Output Connections	IEC C13				